



CM82-EZs-FS

Architectural Specifications

The loudspeaker shall consist of one 203 mm (8.0 in.) low-frequency transducer and one 25.4 mm (1.0 in.) high frequency transducer with a frequency dividing network installed in a sealed enclosure. The low-frequency voice coil diameter shall be 25.4 mm (1.0 in.). The low-frequency transducer shall have a polypropylene cone with a butyl rubber surround. The high-frequency transducer shall be constructed of silk material using a balanced-dome configuration.

Performance specifications of a typical production unit shall be as follows: Usable frequency range shall extend from 82 Hz - 22 kHz, -10 dB. The loudspeaker shall be available for use in 25,- 70.7-, and 100-volt systems. The frequency-dividing network shall have a crossover frequency of 3.0 kHz. Rated power capacity of the components and network shall be at least 64 watts RMS and conform to EIA-426-B testing. Maximum continuous output at 1 meter shall be at least 99.0 dB SPL with the 10 W tap.

The backcan shall be constructed of galvanized steel with an ABS plastic baffle. The grille shall be constructed of painted steel treated with a rust-inhibiting paint adhesive. Shipped complete with UL-listed flex conduit connector, color coded tile bridge (to match color coded backcan label), grille, and paint shield, the integrated in-ceiling speaker is engineered for high performance and rapid installation in plenum spaces. The unit incorporates three additional attachment points for added security and code satisfaction where required.

Installation for the speaker shall be by two-screw blind-mount constant tension fixed-wing assembly and shall attach to ceiling thicknesses ranging from 0.9 mm (0.04 in.) to 40.6 mm (1.60 in.). The external wiring shall be by 4 position ceramic terminal strip, accepting up to 8-gauge wire.

The maximum backcan dimension shall be no more than 95.3 mm (3.75 in.) in height by 245.6 mm (9.67 in.) in diameter. The maximum visible dimensions shall be no more than 8.6 mm (0.34 in.) in height by 298.5 mm (11.75 in.) in diameter. The unit is factory preset to the 10-watt setting in the 70.7-volt operating mode with a tap switch located on the front baffle.

The system shall be the SoundTube CM82-EZs-FS for both low- and high impedance applications.